

# Nutech EcoSafe Range®

Nutech Paint  
Application Instructions & Guidelines  
Nutech EcoSafe Range



## Nu-EcoSafe Paint Brush Restorer

### Features

- Water-based
- Fully biodegradable
- Non-flammable
- Contains no TAPs or HAPs (Toxic/Hazardous Air Pollutants)
- Non-carcinogenic
- Easy clean-up with running water
- Low VOCs
- Non-ozone-depleting
- Not regulated by authorities for Transportation/storage

### Cost effective because:

- Requires much less chemical to achieve desired results

### Typical Properties

<b>Appearance:</b>	Clear liquid	<b>Viscosity (cPs):</b>	N/A
<b>Specific Gravity:</b>	1.06	<b>Shelf Life:</b>	24 months
<b>Boiling Point:</b>	100 °C	<b>Coverage:</b>	N/A
<b>Freezing Point:</b>	0 °C	<b>(theoretical)</b>	
<b>pH (direct reading):</b>	3.5 - 4.5	<b>Worker Health and Safety See MSDS</b>	
<b>VOC content:</b>	70 g/L		
<b>Flash point:</b>	100 °C		

### Typical Uses

#### Typical projects include:

**Nu-Eco PAINT BRUSH RESTORER** has proven to be effective in restoring highly used, dried out paint brushes of epoxy coats and primers, alkyds, non-skid coatings (100% solid content) and the toughest of industrial coatings...

#### Typical projects include:

- DIY projects

Packaging	Sizes Available
Each	1 L Pail
Each	2 L Pail

# Nutech EcoSafe Range®

Nutech Paint  
Application Instructions & Guidelines  
Nutech EcoSafe Range



## Nu-EcoSafe Paint Brush Restorer Applications & Features

### Preparation:

#### (a) Mixing: Do not shake Eco Paint brush restorer

Give the liquid a quick stir with a spatula and it is ready for use..

### Equipment & Tools:

This product is engineered to be used on any old used paint brush.

Pour solution into a hard plastic container (only) and place the brush in the liquid. Leave to soak for at least 1 hour for the dried up paint to soften.

After soaking, plunge the brush up and down to remove the softened paint off the brush. Any remaining paint can be removed by wiping it off with a rag.

The brush can then be run under hot/warm water and then allowed to dry off completely before using again.

The solution can be used twice before disposing of the product.

### Disposal:

Absorb into dry earth or sand.

Transfer to a closable, labeled salvage container for disposal by an appropriate method.

**SAFETY PRECAUTIONS:** Proper safety procedures should be followed at all times while handling the product. Refer to the Safety Data Sheet for important health and safety information before use.

DISCLAIMER: Warranty and Limitation of liability:

#### Warranty

Nutech warrants its products to be free from defects in material and workmanship. Nutech's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Nutech's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account in the invoiced amount of the nonconforming products.

Any claim under this Warranty must be made by Buyer to Nutech in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify Nutech of such non-conformance as required herein shall bar Buyer from recovery under this Warranty.

Nutech makes no other warranties concerning the product. No other warranties, whether express, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall Nutech be liable for consequential or incidental damages.

Any recommendation or suggestion relating to the use of the products made by Nutech, whether in its technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.

#### Limitation of Liability

Nutech's liability on any claim of any kind, including claims based upon Nutech's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or part thereof which gives rise to the claim. In no event shall Nutech be liable for consequential or incidental damages.

#### Important Note

The information given on this data sheet is based on many years experience and is correct to the best of our knowledge. However since the use of our product, surface conditions, weather and a number of other factors are completely beyond our control, we can only be responsible for the quality of our product at the time of dispatch. For more information please contact our Company. As this information is of a general nature, we cannot assume any responsibility in individual cases.